

Tipo de Cabo	Factor de Velocidade	1.2 GHz	2.4 GHz	5.8 GHz
RG-58	66%	0.692 dB/m	1.056 dB/m	1.692 dB/m
RG-8X	78%	0.528 dB/m	0.758 dB/m	1.324 dB/m
LMR-240	84%	0.302 dB/m	0.423 dB/m	0.669 dB/m
RG-213/214	82%	0.331 dB/m	0.499 dB/m	0.938 dB/m
9913	84%	0.171 dB/m	0.253 dB/m	0.453 dB/m
LMR-400	85%	0.157 dB/m	0.223 dB/m	0.354 dB/m
CNT-400 (C2FP)	85%	0.162 dB/m	0.220 dB/m	0.402 dB/m
3/8" LDF	88%	0.138 dB/m	0.194 dB/m	0.266 dB/m
LMR-600	87%	0.102 dB/m	0.144 dB/m	0.239 dB/m
½" LDF	88%	0.089 dB/m	0.128 dB/m	0.216 dB/m
7/8" LDF	89%	0.049 dB/m	0.075 dB/m	0.125 dB/m
1 1/4" LDF	89%	0.036 dB/m	0.056 dB/m	0.092 dB/m
1 5/8" LDF	88%	0.031 dB/m	0.046 dB/m	0.082 dB/m